





Megapixel Color Monitor

Wide viewing angles for clinical data and medical imaging with DICOM calibration function











# Wide Viewing Angles with the IPS Panel, LED Backlight

IPS panel technology provides high brightness, a wide viewing angle and accuracy in color. LED Backlight system contributes more stability in images and energy saving.

## **Color Calibration**

Color calibration function to reproduce colors precise to the original and grayscale compliant with DICOM Part 14 standard.

\* Optional calibration kit CAL-016 is required for calibration.






# Luminance Stabilizing System

The Luminance sensor in back constantly monitors and accurately stabilizes luminance on the screen to optimize image quality.

#### | Multi-interface

CL-R190 provides for two digital interfaces (DVI-D, DisplayPort), and an analog interface (D-Sub mini 15pin).

## Dimensions (mm)






# Specifications

Model Name		CL-R190
LCD Panel	Technology	19" color TFT IPS technology
	Display Area	374.78 mm × 299.82 mm
	Pixel Pitch	0.292 mm × 0.292 mm
	Contrast Ratio	1000 : 1 (typ.)
	Maximum Luminance	250 cd/m² (typ.), 150 cd/m² / 180 cd/m² (calibrated
	Viewing Angle	178° vertical and horizontal
Visual Performance	<b>Native Resolution</b>	VGA (640 × 480) ~ SXGA (1280 × 1024)
	Grayscale	16.77 million colors from a palette of 1.064 billion colors
Interface	Input Signal	Digital : DVI-D, DisplayPort Analog : D-Sub mini 15pin
	Plug and Play	DDC2B compliant
Input Power Supply	Input Power Supply	AC 100 - 250 V, 50 / 60 Hz
	Maximum Power Consumption	22 W (max.)
Features	Calibration Control	Luminance, Gamma, Color temperature (Optional Calibration kit is required)
	OSD Information Display	Model name, Serial No., Total operating time, Calibration settings
Approvals		CE(EN60601-1, EN60601-1-2), VCCI-B, J-Moss, RoHS
Physical Characteristics	Dimensions (W × H × D)	419.6 × 411.3 × 190 mm
	Weight	4.4 kg
	Tilt Stand	Tilt
	Mount	VESA standard (100 mm × 100 mm)
	Security Slot	Anti-theft security slots
Accessories		AC adapter, Power cord, DisplayPort cable, DVI cable, USB cable, Instruction manual

## Interface



• "JVC" is a brand of medical and industrial monitors manufactured and sold by JVCKENWOOD Corporation. • Company names and product names are the registered trademarks of the respective companies. • Product specifications and appearance are subject to change without notice. • Colors in photographs may differ from actual colors due to the printing process. • Images on screens are simulated.



- •Please read the user's manual for safe and proper use.
- Do not expose the product to dust, moisture, steam, or oily smoke. It could cause fire, electric shock, or a failure.

#### Quest International, Inc.

www.questinc.com 60 Parker, Irvine, CA 92618 1.800.231.6777 info@questinc.com

